

5G Single-Use Location and Condition Tracker



LOCATION
Hyper-accurate location data.



CLIMATE MONITORING
Insight into a shipment's environment.



SHIPMENT INTEGRITY
Shock sensors indicate shipment damage.



ASTOUNDING BATTERY LIFE
Exceeds any shipment length requirement.

Tive Solo 5G Single-Use Tracker

The Tive Solo 5G™ is a single or multi-use multi-sensor tracker that measures hyper-accurate location, temperature, humidity, shock, and light exposure of shipments. Using the latest global cellular, WiFi, and GPS technology and on-board sensors, the Solo 5G reports real-time sensor data to the Tive SaaS Platform. From there, logistics professionals actively manage shipments and eliminate preventable shipment delays and damage. A single button activates the tracker, and there's no need to return it, eliminating complex reverse logistics operations.



 **Committed to Sustainability** The Tive Solo 5G can be recycled with Tive's Green Program

Designed for these shipments



Cold Chain



High-Value



Industrial



Automotive



Time Sensitive

Specifications

Tive Solo Single-Use Tracker



Actual Size

CASE SPECIFICATIONS

Case Material:
UL 94-V0 flame retardant plastic

Dimensions:
96 mm x 58 mm x 19.5 mm

Weight:
3.5 ounces (100 grams)

Mounting:
3M Adhesive, Cable Tie

IP Rating:
IP67

SENSORS

Condition Sensors:
Temperature, Humidity, Light, Motion, Shock, With configurable thresholds for alerts

Temperature Accuracy:
±0.5°C, NIST Traceable
ISO 17025 calibration certificate
(3-points) available
-20°C to 60°C

CERTIFICATIONS

FCC, CE, RoHS, UN38.3

GLOBAL CELLULAR CONNECTIVITY

Transmission Type:
LTE Cat-M1 (4G/5G), fallback to GSM (2G)

Cellular Coverage:
Global bands: B1/B2/B3/B4/B5/B8/
B12/B13/B18/B19/B20/B25/B28

MEMORY STORAGE

Up to 25,000 records

POWER SOURCE

Rechargeable Lithium-Ion battery
(3.7V, 2600 mAh / 9.62Wh capacity)
Charging Method: USB Micro

Battery Life:
Over 90 days (60 mins reporting interval)
Shelf life of 180 days

LOCATION

Location Method:
Cellular, GPS, Wi-Fi Geolocation

Location Accuracy:
< 500 m

WIRELESS SENSOR SUPPORT

Tive Temperature Beacon (TT-6000)

FOR FURTHER INQUIRIES ABOUT THE TIVE SOLO, PLEASE CONTACT SALES@TIVE.COM

Condition Sensors



Temperature



Light



Humidity



Shock



Motion